


OKA NT 4x4 Pop-Top Camper Van

EURO 5

Technical data



Dimensions mm (Fully fuelled, unladen. Drawing may depict optional equipment)

OL Overall Length	OH Overall Height	OW Overall Width	CW Cab Width	WM Width Mirrors
5661	2508	2000	1900	2340
WB Wheelbase	FOH Front O'hang	ROH Rear O'hang	FT Front Track	RT Rear Track
3190	1101	1370	1664	1664

Engine

Emission class	EURO5
Type	Cummins ISBe5
No. and arrangement of cylinders	4 in-line
Technology	SCR
Diesel direct injection turbocharged & intercooled	4 stroke
Power output	kW (hp) 136 (185)
At rated speed	rev/min 2500
Maximum torque	Nm 700
At rated speed	rev/min 1200-1700
Displacement	cm ³ 4500
Coolant – water	
With thermostat	Thermostatic fan
Fuel tank	litres 120
AdBlue tank	litres 43

Transmission

Clutch: 330mm single plate hydraulic

Gearbox: Tremec TR4050 manual

all synchromesh, 5 gears forward, 1 reverse

Ratio spread	5.81-0.77:1
--------------	-------------

Optional Gearbox:

Allison 1000 series automatic with park pawl

6 forward gears, 1 reverse

Ratio spread	3.10-0.61:1
Torque converter stall	1.73:1

Transfer box

OKA HD250

Ratio	High 1.00:1
	Low 2.00:1

Available combinations	4 High
	4 Low
	Neutral
	2 High

Axles

Front axle: OKA heavy duty beam type - drive steer with hub step

Ratio	4.62:1
Capacity	kg 3200

Rear axle: OKA heavy duty beam type

Ratio	4.62:1
Capacity	kg 3800

Brakes

Service brake: Ventilated disc brakes front and rear. Power boosted air over hydraulic

Diameter front	mm 350
Diameter rear	mm 350

Park brake: Drum type on transfer case – spring application, air release

Drum diameter	mm 178
---------------	--------

Steering

Power assisted variable ratio with damper

Suspension

Front: 12 leaf OKA Flex suspension with single rate semi-elliptic multi-leaf springs and Aeon second stage helper springs. High performance long-stroke double acting shock absorbers

Rear: 13 leaf OKA Flex suspension with dual rate semi-elliptic multi-leaf springs and Aeon third stage helper springs. High performance long-stroke double acting shock absorbers.

Wheels and tyres

Wheels: 4 road wheels (single on rear)

Rim size: 19.5"x 8.25" one piece rim

Tyres: 285/70R19.5 Continental HDR

Spare wheel and tyre

Chassis

Box section straight rail

Flat welded ladder frame construction

Electrics

System: 24 V, 90 Amp alternator.

Lighting: Dual beam headlamps and driving lights, Indicators and reversing lights.

Cab (standard equipment)

Forward control 2 door welded construction, with zinc coated steel sheet panels, built to ROPS safety standard (AS1636-1984)

Laminated windscreen, 2 speed + intermittent wipers and washers. Rear view mirrors.

2 seats with seatbelts (single action, detachable for easy servicing).

Steering lock, demister, interior

sunvisors, glove box, cigarette lighter. Driver's cab air-conditioning. Radio AM/FM/CD

Gauges: Speedometer, trip meter, odometer, tachometer, fuel level, water temperature, oil pressure, volt meter, clock

Warning lights: Oil pressure, water temp, charge high beam, indicators, brake failure, 4WD

Engagement, diff-lock engagement.

Weights (basic execution)

Gross vehicle mass GVM	kg	6500
Permissible front axle load	kg	3200
Permissible rear axle load	kg	3800
Tare weight*	kg	4850
Gross Payload*	kg	1650
GCM	kg	9000
Max braked trailer weight	kg	4500

*Tare and payload are indicative and

do not take into account weight of options

Performance indicator

• Maximum cruising	Km/h	120
• Maximum gradient	% m	60
• Turning circle		14.5

Camper Van module

4 bay body fully fabricated from zinc coated steel with box section frame. Skin panels welded and glued in place.

- Rear bottom-hinged tailgate
- Nearside door with fixed window
- Each bay glazed - fixed windows
- 12mm marine ply floor with vinyl covering
- Pop-top (manual control)

Optional wheel and tyres

- Fitted 285/70R19.5 Continental HDR tyres on bolt-together rims 8.25" x 19.5"
 - Fitted 305/70R19.5 Continental HDR tyres on one piece rims 8.25" x 19.5"
 - Fitted 305/70R19.5 Continental HDR tyres on bolt-together rims 8.25" x 19.5"
 - Spare one price rim size 8.25" x 19.5"
 - Spare bolt-together rim 8.25" x 19.5"
 - Spare tyre 285/70R19.5 or 305/70R19.5
- Additional spare wheel and tyre assembly to match tyre equipment fitted
- Swing-out spare wheel carrier
- Winch type spare wheel carrier

Optional accessories

- Front axle differential lock
- Rear axle differential lock
- Air-conditioning ducted to rear of cab for body - various possibilities of ducting / fans
- Bull bar
- Tow bar
- Free wheeling hubs
- Cruise control (manual or auto)
- Hub step – rear wheels
- External sunvisor
- Tow bar
- Fire Extinguisher
- Auxiliary fuel tank 170 litres
- Water tank 80 litres
- Auxiliary battery system
- Electric winch – capacity 15000 lb (66.7kN)
- Radio AM/FM/CD with PA system
- Speed limiter setting
- Tropical roof + rack
- Auto air step
- Rear barn doors
- Sliding side windows (except door)
- Blanked windows to choice
- Rust proofing
- Light bar with beacons and worklight
- First aid kit
- Tachograph
- Hour meter
- Spotlights

Special Vehicle Options


- 20" tyres to customer preference
- CTIS (central tyre inflation system) kit on 8.25" x 19.5" rims with beadlock
- CTIS (central tyre inflation system) kit on 9.00" x 20" rims with beadlock
- Air beadlock for 8.25" x 19.5" 1 piece rim
- Air beadlock for 9.00" x 20" 3 piece rim
- Air beadlock for 8.25" x 19.5" bolt-together
- Air beadlock for 9.00" x 20" bolt-together
- Rubber beadlock (for 20" split rims)
- Exit hatch on driver's cab
- NATO black-out lighting
- NATO trailer hitch and trailer plugs

Optional seating


- Vinyl seat trim
- Holdsworth seat trim
- Rear fixed seat vinyl
- Rear fixed seat wool moquette
- Rear fixed seat Holdsworth
- Rear reclining seats vinyl
- Rear reclining seats wool moquette
- Rear reclining seats Holdsworth
- Rear mining seats vinyl

Optional seating layout

Optional 6 seats



Optional 7 seats



OKA Australia has a policy of continuous product improvement and reserves the right to alter any specification without notification.

This document may not be shown, lent or copied without express permission of the company. All rights reserved